

**NAME**

CURLOPT\_FTPSSLAUTH – set order to attempt TLS vs SSL when using FTP

**SYNOPSIS**

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_FTPSSLAUTH, long order);
```

**DESCRIPTION**

Pass a long using one of the values from below, to alter how libcurl issues "AUTH TLS" or "AUTH SSL" when FTP over SSL is activated. This is only interesting if *CURLOPT\_USE\_SSL(3)* is also set.

Possible *order* values:

CURLFTPAUTH\_DEFAULT

Allow libcurl to decide.

CURLFTPAUTH\_SSL

Try "AUTH SSL" first, and only if that fails try "AUTH TLS".

CURLFTPAUTH\_TLS

Try "AUTH TLS" first, and only if that fails try "AUTH SSL".

**DEFAULT**

CURLFTPAUTH\_DEFAULT

**PROTOCOLS**

FTP

**EXAMPLE**

TODO

**AVAILABILITY**

Added in 7.12.2

**RETURN VALUE**

Returns CURLE\_OK if the option is supported, and CURLE\_UNKNOWN\_OPTION if not.

**SEE ALSO**

*CURLOPT\_USE\_SSL(3)*, *CURLOPT\_FTP\_SSL\_CCC(3)*,