

CURLOPT_GSSAPI_DELEGATION(3) curl_easy_setopt options CURLOPT_GSSAPI_DELEGATION(3)

NAME

CURLOPT_GSSAPI_DELEGATION – set allowed GSS-API delegation

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_GSSAPI_DELEGATION, long level);
```

DESCRIPTION

Set the long parameter *level* to `CURLGSSAPI_DELEGATION_FLAG` to allow unconditional GSSAPI credential delegation. The delegation is disabled by default since 7.21.7. Set the parameter to `CURLGSSAPI_DELEGATION_POLICY_FLAG` to delegate only if the `OK-AS-DELEGATE` flag is set in the service ticket in case this feature is supported by the GSSAPI implementation and the definition of `GSS_C_DELEG_POLICY_FLAG` was available at compile-time.

DEFAULT

`CURLGSSAPI_DELEGATION_NONE`

PROTOCOLS

HTTP

EXAMPLE

TODO

AVAILABILITY

Added in 7.22.0

RETURN VALUE

Returns `CURLE_OK` if the option is supported, and `CURLE_UNKNOWN_OPTION` if not.

SEE ALSO

`CURLOPT_HTTPAUTH(3)`, `CURLOPT_PROXYAUTH(3)`,