

CURLOPT\_TLSAUTH\_PASSWORD(3) curl\_easy\_setopt options CURLOPT\_TLSAUTH\_PASSWORD(3)

## NAME

CURLOPT\_TLSAUTH\_PASSWORD – TLS authentication password

## SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_TLSAUTH_PASSWORD, char *pwd);
```

## DESCRIPTION

Pass a char \* as parameter, which should point to the zero terminated password to use for the TLS authentication method specified with the *CURLOPT\_TLSAUTH\_TYPE(3)* option. Requires that the *CURLOPT\_TLS\_USERNAME(3)* option also be set.

## DEFAULT

NULL

## PROTOCOLS

All TLS-based protocols

## EXAMPLE

TODO

## AVAILABILITY

Added in 7.21.4

## RETURN VALUE

Returns *CURLE\_OK* if the option is supported, *CURLE\_UNKNOWN\_OPTION* if not, or *CURLE\_OUT\_OF\_MEMORY* if there was insufficient heap space.

## SEE ALSO

*CURLOPT\_TLSAUTH\_TYPE(3)*, *CURLOPT\_TLSAUTH\_USERNAME(3)*,